









PRODUCT HIGHLIGHTS



Compliant to EN45545-2
Fire protection on railway vehicles



Excellent weather resistance & durability



Unparallel accoustic isolation



Outstanding sealing durability and life cycle



Solution based customization available*



High elasticity & lasting restoring forces

TECHNICAL DATA	
Material	Fire resistant material EPDM
Hardness	Range from 60, 70, 80 Shore A
Conformity to standards	EN 45545-2, ISO 14001, ISO 45001, ISO 9001, DIN 5510-2, NF F 16-101, EcoVadis Gold

^{*}Customization available. Please contact your sales representative for further information.

Va. 10.2021 All specifications, numbers, calculations, test values, and data mentioned here – which are the basis for our customer consultation – are in accordance with the latest engineering standards. As the operating conditions have an influence on product application, it is the sole responsibility of the customer to check the application conditions of each individual case, and whether the specified quality criteria of our products are adequate for the intended purpose. Improper use, excessive loading, or exposure to impermissible media can impair the product's function. The pictures and graphics shown are only representative images. No liability is accepted for mistakes or printing errors, and data is subject to change at any time. Copying and distribution in any form whatsoever, in whole or in part, only with the express written consent of Semperit. Copyright © Semperit 2021. All rights reserved.

SEMPERIT ()

CONTACT US

Semperit Technische Produkte Gesellschaft m. b. H. Triester Bundesstraße 26, 2632 Wimpassing, Austria Tel.: +43 2630 310 0, E-mail: sales.ses@semperitgroup.com www.semperitgroup.com

